

## ENERGY DATA

CODE 16216

### CA 100 V0 D EP

In-line centrifugal fans in self-extinguishing plastic



ATTRIBUTO	VALORE ATTRIBUTO
Supplier's name or trade mark	Vortice
Specific Energy Consumption class SEC in average climate zone	F
Specific Energy Consumption class SEC average [kWh/m2a]	-6,3
Specific Energy Consumption class SEC cold [kWh/m2a]	-15,4
Specific Energy Consumption class SEC warm [kWh/m2a]	5,7
Declared typology	UVR-U: unidirezionale
Type of drive	velocità multiple: VM
Type of heat recovery system HRS	assente
Thermal efficiency of heat recovery at reference air flow [%]	NA
Maximum flow rate [m3/h]	185
Electric power input of the fan drive, including any motor control equipment, at maximum flow rate [W]	77,0
Sound power level LWA [dB(A)]	77
Reference flow rate [m3/s]	0,0360
Reference pressure difference [Pa]	100
SPI [W/(m3/h)]	0,34749
Control factor CTRL	1
Control typology	manuale
Maximum internal leakage rates [%]	NA
Maximum external leakage rates [%]	2,1
Mixing rate	NA
Position and description of visual filter warning	NA
Airflow sensitivity to pressure variations at + 20Pa and - 20 Pa	NA
Indoor/outdoor air tightness [m3/h]	NA
Annual electricity consumption (AEC) [kWh electricity/a]	435
AHS average Annual heating saved [kWh primary energy/a]	1715
AHS cold Annual heating saved [kWh primary energy/a]	2732
AHS warm Annual heating saved [kWh primary energy/a]	632